

### **DECLARATION OF PERFORMANCE**

# Nº HEL-CPR-3212

1. Product Identification:

### Render Mortar – TECTOR NATURAL BASE (GP-CSII-W0)

2. Intended Uses of the Product:

#### Common render mortar for exterior use

3. Manufacturer:

Holcim España S.A.U. Avda. Manoteras, 20 Edificio Tokio- 1ª planta 28050 Madrid - Spain

4. Assessment and Verification System of Performance Consistency:

## System 4

5. Declared Performances:

Essential Characteristics	Performance Compliance	Harmonized Technical Specifications
Compressive strength	1.5 - 5 N/mm <sup>2</sup>	EN 998-1:2016
Reaction to fire	Class A1	
Water absorption	W2	
Adhesión	>0,1 N/ mm <sup>2</sup> FP:B	
Water vapor permeability	μ<6	
Thermal conductivity (λ10 dry)	0.47 W/mK (tabulated mean value; P=50%)	
Compressive strength	CSI	
Durability	NPD	
Hazardous substances	See safety data sheet	

6. The performances of the product identified in section 1 conform to the declared performances in section 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in section 3.

Signed on behalf of the manufacturer by:

Benito Carrión Gómez. Quality & Zone Mortar Manager

Hellín, March 12, 2019