

THERMAL AND PHONIC INSULATION **PURE WOOL**

Insulation of unused attics and floors

PROPERTIES

- Sheep wool is a sustainable solution for the absorption of FORMALDEHYDES AND VOC.
- •Excellent thermal insulation. Sheep live in cold climates but also in hot climates and produce wool to protect themselves from these extreme temperatures.
- Very good hygrometric regulation capacity without loss of insulating qualities.

IMPLEMENTATION

- Very easy manual cutting.
- •Thanks to the natural properties of our high quality wool, the compressed product will regain its volume over time. The thickness right out of the package is not not significant.
- •A Unroll on a floor: take care to avoid thermal bridges by shifting or crossing the layers between them.
- •To install in horizontal boxes: ensure that the product fills the box well by cutting the widest strips a few centimeters and stapling regularly on the sides.
- •Respect the rules for implementing permeable walls for the correct operation of this insulator.

H		1000/			
Composition	100% sheep wool				
Treatment	Konservan P10 Moth Repellent				
Width (cm)		60/200			
Length (m)	8	10	12	14	
Density (kg/m3)	12.5	13	13.75	18	
±15% Thickness	12	10	8	5	
(cm) ±15% Thermal resistance R (m2°C/W3).42		2.85	2.28	1.42	
Thermal conductivity λ (W/m°C)		0.035			
Specific heat capacity p (J/Kg.K)		00			
Water vapor permeabilityµ	ermeabilityµ		1 to 2		
Wool flash point (°C)		560			
Hygroscopic capacity		Up to 33% of its weight			
Fire classification		Self-extinguishing - Class B2			
References	FLBKVNT1500-60R	FLBKVNT1300-60R FLBKVNT1100-60R FLBKVNT 900-60R			

This information is given for information purposes only, as these products are not currently subject to any standards.

103V01-032019





FLBKVNT 1500-200R FLBKVNT 1300-200R FLBKVNT 1100-200R FLBKVNT 900-200R









100% Sheep Wool Insulation 100% ecological



Very efficient thermal resistance

ለ: 0.035



Absorption of formaldehydes and other VOCs



Naturally self-extinguishing (class B2)



Regulation of humidity and water vapor







I03V01-032019

