




VIEW FROM SPIGOT SIDE





SECTION A-A



VIEW FROM SOCKET SIDE



VIEW FROM UNDERSIDE



IMPORTANT:
THE ANNULI (A) 2.0 MIN. BETWEEN SOCKET
AND SPIGOT JOINT IS CRITICAL FOR THE
PERFORMANCE OF THE JOINT.

- 1) GUTTER TO BE STRAIGHT - MAX PERMITTED BOW 2.5mm/metre.
- 2) EXCESSIVE UNDULATION NOT ACCEPTABLE ON GUTTER EDGES.
- 3) COLD LAPS OR THROUGH HOLES NOT PERMITTED.
- 4) GUTTER SURFACE TO BE CLEAN AND FREE OF CONTAMINENTS OR RUST PRIOR TO PAINTING.
- 5) IT IS ESSENTIAL THAT THE SOCKET AND SPIGOT ENDS FOR BOTH GUTTERS AND FITTINGS ARE CHECKED FOR COMPATIBILITY THROUGH A RECORDED QUALITY SYSTEM BEFORE LEAVING THE MANUFACTURER.

ALL MARKINGS TO BE 8MM MIN CLEAR OF
SLOT TO ALLOW ROOM FOR FIXINGS

UNCONTROLLED COPY

Copyright and Design right

This confidential drawing is the sole property of Hargreaves Foundry Group Companies and must not be reproduced or distributed to any third party without written permission. It must only be used for the purpose for which it has been issued and may be withdrawn upon request. The validity of the drawing is only guaranteed at the time of issue and is subject to change without notice.

ALL DIMS IN mm

WATER LANE
SOUTH PARADE
HALIFAX
WEST YORKSHIRE
HX3 9HG



TEL: (44) 01422 330607
FAX: (44) 01422 320349
E-MAIL: info@hargreavesfoundry.co.uk

TITLE 125mm Half Round Gutter 6ft		
MATERIAL BSEN 1561 Grade:EN-GJL-150		
SCALE 1:2 A3	DRAWN S Clarke	CHECKED P Gill
DATE 15/04/24	REF No -	REV. 5
DWG No HR5001		