



Insulating sheathing and render board - optimised cold protection and high board thicknesses

- 4-fold function: cold protection, rain protection, wind protection, render board
- Can be used in conjunction with STEICO air-injected insulation
- Particularly economical – just one type of panel for roof constructions (from 1880 mm in length) and rendered façades (from 40 mm in thickness)
- Also ideal for renovation projects thanks to high board thicknesses and very good insulation performance
- Diffusion-open for increased structural safety
- Wood from responsible forestry - PEFC certified

Application area



- Provides temporary weather protection
- Plaster coatable wood fibre boards for external use
- Wall construction panel for timber construction in combination with ventilated rainscreen façades
- Can be used from a roof pitch of $\geq 14^\circ$

Technical data

Produced and supervised according to	EN 13171, EN 14964
Board designation	WF – EN 13171 – T5 – DS(70,-)2 – CS(10\Y)100 – TR20-WS1,0 – MU3, EN-14964-IL
Fire class (RTF) according to EN 13501-1	E
Permanent temperature range [°C]	≤ 100
Declared thermal conductivity [W/(m*K)]	0.040
Density [kg/m³] (approx.)	140
Water vapour diffusion resistance factor μ	3
Short-term water absorption [kg/m²]	≤ 1.0
Specific heat capacity [J/(kg*K)]	2,100
Compressive strength at 10% compression δ_{10} [N/mm²]	0.1
Compression strength [kPa]	≥ 100
Tensile strength perpendicular to face [kPa] (approx.)	≥ 20
Manufacturing process	dry process / utilization polyurethane resin for panel bonding
Permissible roof pitch without additional measures [°]	≥ 14
Maximum undercutting of the standard roof pitch [°]	8
Ingredients	Wood fibre, polyurethane resin, paraffin wax
Declared level of airflow resistance [(kPa*s)/m²]	≥ 100
Outdoor exposure [weeks]	4
Bonded carbon [kg CO ₂ equivalent./m³] (approx.)	200

Additional technical data

Thickness [mm]	Declared thermal resistance [(m²*K)/W]	s _d value [m]
60	1.50	0.18
80	2.00	0.24
100	2.50	0.30
120	3.00	0.36
140	3.50	0.42
160	4.00	0.48
180	4.50	0.54
200	5.00	0.60

Forms of delivery

Handy formats, e.g. for construction site assembly

Thickness [mm]	Edge profile	Length [mm]	Width [mm]	Length net [mm]	Width net [mm]	Number/pal. [pcs.]	Coverage/pal. gross [m²]	Coverage/pal. net [m²]
60	T+G	1325	600	1300	575	38	30.210	28.405
60	T+G	1880	600	1855	575	36	40.608	38.399
60	T+G	2230	600	2205	575	36	48.168	45.644
80	T+G	1325	600	1300	575	22	17.490	16.445
80	T+G	1880	600	1855	575	28	31.584	29.866
80	T+G	2230	600	2205	575	28	37.464	35.501
100	T+G	1325	600	1300	575	22	17.490	16.445
100	T+G	1880	600	1855	575	22	24.816	23.466
100	T+G	2230	600	2205	575	22	29.436	27.893
120	T+G	1880	600	1855	575	18	20.304	19.199
140	T+G	1880	600	1855	575	16	18.048	17.066
160	T+G	1880	600	1855	575	14	15.792	14.933
180	T+G	1880	600	1855	575	12	13.536	12.800
200	T+G	1880	600	1855	575	12	13.536	12.800

Weight and packing

Handy formats, e.g. for construction site assembly

Thickness [mm]	Edge profile	Length [mm]	Width [mm]	Weight/m ² [kg]	Weight/pcs. [kg]	pac./pal. paper/cardboard (approx) [kg]	pac./pal. plastic (approx) [kg]	pac./pal. wood (approx) [kg]	Weight./pal. (approx.) [kg]
60	T+G	1325	600	8.40	6.3	4.10	1.1	30.7	275
60	T+G	1880	600	8.40	9.0	4.40	1.1	25.5	360
60	T+G	2230	600	8.40	10.7	0.05	1.0	28.4	410
80	T+G	1325	600	14.00	10.5	4.10	1.1	30.7	270
80	T+G	1880	600	11.20	11.9	4.40	1.1	25.5	370
80	T+G	2230	600	11.20	14.2	0.05	1.0	28.4	425
100	T+G	1325	600	14.00	10.5	4.10	1.1	30.7	270
100	T+G	1880	600	14.00	14.9	4.40	1.1	25.5	365
100	T+G	2230	600	14.00	17.8	0.05	1.0	28.4	415
120	T+G	1880	600	16.80	17.9	0.05	1.0	25.5	350
140	T+G	1880	600	19.60	20.9	0.05	1.0	25.5	360
160	T+G	1880	600	22.40	23.9	0.05	1.0	25.5	360
180	T+G	1880	600	25.20	26.9	0.05	1.0	25.5	350
200	T+G	1880	600	28.00	29.9	4.40	1.1	25.5	395

Notes

Storage

- Store wood fibre boards horizontally, flat and dry
- Protect edges from damage
- Only remove the film packaging when the ambient climate is dry and keep the pallet packing label
- Maximum stacking height: 3 pallets

Disposal

Waste cuttings:

- Waste code according to 2014/955/EU: 03 01 05

Dismantling:

- Waste code according to 2014/955/EU: 17 02 01

Cutting

- The boards can be cut to size using the STEICO *isoflex cut combi* cutting table or a band saw, circular saw, jigsaw and other wood-cutting tools.

Occupational health and safety

- STEICO wood fibre boards can be walked on directly above a rafter or joist support, however they cannot be used as the primary walking surface
- To ensure that the roof can be walked on at all times, it is advisable to lay the battens at the same time.
- Additional fall protection (man safe systems) should be used in line with national guidelines
- Suitable protective measures must be taken when cutting the wood fibre insulation boards. (dust extraction, dust mask)
- HSE guidance on the safe cutting of timber and the management of wood dust should be followed

Building moisture

- Condensation on the side of the panel facing the room during the construction phase disrupts (hinders) the diffusion flow.
- Excess moisture caused by e.g. fresh screed, plaster, or paint must be removed by ventilation
- Dry air must be ensured inside the building during the construction phase.

Installation

Installation in roof and wall areas / plaster base board

- Please observe the processing instructions under the following link: <https://www.steico.com/en/technical/installation>

Additional information

- The maximum weight of the entire render system is 25kg
- Gluing brick slips onto the plaster base board / plaster system is not permitted
- STEICO*special dry* with T&G has a water-repellent surface - may be used without additional weatherproof membranes behind rear-ventilated façades



Certificates and quality management



☰ Caption

other abbreviations

pal. Pallet
T&G Tongue and Groove
pac. Packaging
approx. Approximately
SE square edge
Pcs. Pieces
UDP-A sarking and sheathing board type A

Responsible for content

STEICO UK Ltd
Unit 3 Eden Brae Business Park, Dunstable Road
Caddington LU1 4FF
Great Britain
Web: www.steico.com
Mail: info@steico.com

Version: 1

Date: 2025-05-12

The contents of this document have been prepared with the utmost care. However, applicable regulations can change. STEICO accepts no liability for the accuracy, completeness, or current applicability of the content. Application areas may vary in the detailing. Always verify the suitability of our products for the specific intended use.

This document is valid in the following countries:
United Kingdom, Republic of Ireland

The currently valid version can be found at: www.steico.com/tds_steicospecialdry_gbr-irl_en