

STEICO *multi nail*

Nail tight tape



Nail tight tape for additional sealing measure on counter battens

- Single-sided self-adhesive, excellent adhesive properties
- Resistant to ageing
- Easy handling
- High elasticity

Application area



- Additional sealing measure for screw or nail connections of the counter battens when using STEICO *multi UDB* or STEICO *safe* as underlayment

Technical data

Temperature resistance [°C]	-40 / +80
Processing temperature [°C]	≥ +5
Volume weight [kg/m³] (approx.)	30
Lengthwise tensile strength [N/mm²]	0,34
Transverse tensile strength [N/mm²]	0,22
Lengthwise stretch at break	135
Transverse stretch at break	115
Material	Closed cell polyethylene

Forms of delivery

Supplied in handy boxes

Length [mm]	Width [mm]	Number/pack. [pcs.]
30000	50	10
30000	80	6

Weight and packing

Supplied in handy boxes

Thickness [mm]	Length [mm]	Width [mm]	Weight/m² [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
3	30000	50	0.01	0.2	2.60	0.60
3	30000	80	0.01	0.3	2.60	0.60

Notes

Storage

- Store in a dry place, protected from dirt, sun and moisture

Ingredients

- Cell-closed polyethylene with synthetic rubber

Disposal

- dispose with normal construction waste, observe applicable legal guidelines

Cutting

- Sharp knife or other suitable cutting tool

Installation

- The substrate must be clean, dust-free and dry
- The one-sided self-adhesive tape is applied directly from the roll and fixed to the STEICO*multi UDB* underlayment in the area of the counter-battens.
- The counter-batten is then positioned directly over the applied tape and mechanically fastened (nails and screws).

☰ Caption

other abbreviations

pal. Pallet
T&G Tongue and Groove
pac. Packaging
approx. Approximately

Responsible for content

STEICO UK Ltd
Unit 3 Eden Brae Business Park, Dunstable Road
Caddington LU1 4FF
Great Britain
Web www.steico.com
Mail: info@steico.com

Version: 1

Date: 2025-05-12

The contents of this document have been prepared with the utmost care. However, applicable regulations can change. STEICO accepts no liability for the accuracy, completeness, or current applicability of the content. Application areas may vary in the detailing. Always verify the suitability of our products for the specific intended use.

This document is valid in the following countries:
United Kingdom, Republic of Ireland

The currently valid version can be found at: www.steico.com/tds_steicomulti_nail_gbr-irl_en